SONEX CLEAN PANELS - FAQ

- How are Sonex Classic Panels cleaned?
 - Universal instructions for cleaning Sonex products include the following steps:
 - Always wear white cotton gloves when handling the products
 - Contaminated air and dust particles can penetrate the surface of the open-cell foam material. Prior to starting the HVAC system, remove construction dust from the interior of the building. Proper supply and return air filtration and regular HVAC filter maintenance minimize soiling
 - General cleaning:
 - Delicately vacuum or dust regularly
 - HPC-coated Sonex products:
 - Spray clean, soft cloth with a gentle-purpose glass and surface cleaner.
 Squeeze excess cleaner from cloth prior to treatment. Carefully wipe away smudges. DO NOT rub aggressively, AVOID excessive moisture and NEVER soak product with water damage to the HPC coating or substrate can occur
- What colors are Sonex Classic Panels available in?

Natural willtec®	HPC-coated* willtec				
white	black/black onyx	medium grey/graphite			
1.44 1.44 1.44					
grey	light grey/grey mist	light blue/sky			
colortec®					
charcoal	white/arctic white	ivory/eggshell			
	almond				

- What is a Sonex Classic Panel
 - SONEX Classic Panels feature a modified anechoic wedge design for cost-effective, yet impressive sound control.
 - The unique geometric shape of the surface pattern on these panels provides optimum deflection of sound waves, making them an excellent choice for recording and broadcast studios.
 - These versatile panels can also be used in listening rooms, restaurants, production areas and other locations where sound absorption is critically important.

FAQ

- Regardless of the finish option, pinta's exclusive willtec foam is Class 1 fire-rated, according to ASTM E 84 for flame spread and smoke density. willtec natural and colortec meet the corner burn test UL 1715.
- These panels can easily be mounted to any wall or ceiling surface with pinta's acouSTIC water-based adhesive.



Color	Sheet Size	Thickness	Sheets Per Box	Coverage	Order Number	
Natural White	24" x 48"	2"	8	64 sq. ft.	SOC-2	\$303
Natural Grey	24" x 48"	2"	8	64 sq. ft.	SOC-2	\$253
Charcoal colortec	24" x 48"	2"	8	64 sq. ft.	COC-2	\$305
Charcoal colortec Premium	24" x 48"	2″	8	64 sq. ft.	COC-2P	\$351

• What sizes are Sonex Classic Panels available in?

SONEX Classic Panels

• How are Sonex Classic Panels installed?

- Wall mounted
 - Sonex Classic Panels can be mounted to the wall using acouSTIC adhesive (see accessories page) and hold in place by impalers to secure bond in place throughout the drying process

- Note: It is suggested to start at the bottom perimeter of the walls and work your way up towards the top
- Foam mounted
 - If applied on top of existing flat surface melamine foam you will want to use acouSTIC adhesive (see accessories page) and hold in place by spikes through the side of the wedge to secure bond in place throughout the drying process
 - Note: It is suggested to start at the bottom perimeter of the walls and work your way up towards the top
- PSA (pressure sensitive adhesive) is available for this product. This is an adhesive backing applied directly to the product face being adhered to your desired surface. A peel away sheet will be removed by the installer to reveal the PSA and be applied directly to the surface it is being mounted to.
- What kind of noise reduction levels do Sonex Super and Max Wedges offer?

Finish	Thickness	Coefficients per ASTM C423-90					C423-90a		Manatian
		125Hz	250Hz	500Hz	1kHz	2kHz	4kHz	NRC	RC Type
Natural (white and grey)	2"	0.05	0.31	0.81	1.01	0.99	0.95	0.80	Α
colortec (charcoal)	2"	0.05	0.31	0.81	0.96	0.97	0.97	0.75	Α
colortec premium (charcoal)	2"	0.05	0.31	0.81	0.96	0.97	0.97	0.75	А

Sound Absorption

• Can Sonex Classic Panels withstand a moist or humid environment?

- Yes!
- Sonex Classic Panels are manufactured from Willtec® foam giving them the ability to maintain their integrity in moist or humid environments without sagging

• Can I buy them individually?

 \circ Sonex Classic Panels are sold 8 sheets to a box.

	Chaot		Chaota		Order	ſ
Color	Sheet Size	Thickness	Sheets Per Box	Coverage	Order Number	
Natural White	24" x 48"	2"	8	64 sq. ft.	SOC-2	\$303
Natural Grey	24" x 48"	2"	8	64 sq. ft.	SOC-2	\$253
Charcoal colortec	24" x 48"	2"	8	64 sq. ft.	COC-2	\$305
Charcoal colortec Premium	24" x 48"	2"	8	64 sq. ft.	COC-2P	\$351

SONEX Classic Panels

• How much coverage would either Sonex Super or Max Wedges provide?

- Sonex Classic panels have the capability to provide 64 sq. ft. of coverage per box.
- What environments Sonex Classic Panels best suited for?
 - Common applications for Sonex Classic Panels include:
 - Recording and Broadcast Studios
 - Listening Rooms
 - Machine Enclosures
 - Print Shops
 - Indoor Firing Ranges
 - Museums or Interactive Display Areas
 - Clubs, Bars, and Restaurants

