

Door Gasket

This Quality Basic Door Gasket with enhanced solid neoprene seal will ensure a secure seal around the header and jambs of door frames. Door gasket is rated for fire, smoke and sound filtration. Available in three anodized finishes and is custom cut to size.

- ✓ Product complies with the following ANSI / BHMA Codes:

- Head and Jamb Application: R3B164
- Applied Stop Application: J32120

Dimensions: Casing measures .563" x .351". It is recommended for gaps up to .125"

Seal: This door gasket is fitted with an enhanced Solid Neoprene Seal. The extruded bulb and finger design has great compression properties. The protruding lip ensures the seal is properly maintained, even if the door is slightly warped, due to aging or improper installation.

Casing: Casing is made of high quality .070" thick anodized aluminum that will retain its color and shape, even through constant usage.

Installation: Door gasket is designed to be installed directly onto a door stop. The casing is drilled with slotted screw holes to allow for slight adjustment during installation. All installation screws are provided, and screws are colored to coordinate with casing.

Additional Applications: Can also be used for window soundproofing. Simply install onto sill to seal gap between sill and window pane.

Compliance Details: Gasket is rated for fire, smoke and sound filtration and is UL Listed.

Anti-Ligature Feature: Product is available with Zero's Anti-Ligature feature. Seal is slotted to prevent gasket from being used for anything other than its intended purpose.

FIRE AND SMOKE RATINGS



UL listed



ITS Warnock Hersey listed



10B Classified up to 90 minutes



Category H Classified under UL 1784, listed up to 180 minutes

